

CAT6 STP LOADED PATCH PANEL

D-Link Category 6 STP patch panels are eight ports RJ-45 modules applied and suitable for 22-26 AWG stranded and solid wire, compatible with both 110 & Krone punch down tools. D-Link STP patch panels terminate 4 pairs STP cable and are rack mounted. They are complied with the ANSI/TIA/EIA 568B.2-1 standard



SPECIFICATIONS

Identification:	ID plate, PVC, transparent color with paper ID Bracket: ABS+PC, UL-94V-0
Panel:	SECC, 1.2mm thickness with optional color painted
RJ45 Jack:	Housing: PBT + glass fiber, UL-94V-0 Contact Bracket: PBT + glass fiber, UL-94V-0
RJ45 Jack Contact	Material: Phosphor bronze with nickel plated Finish: 50 micro-inches Gold plated on plug contact area
RJ45 Jack Shield:	Bronze with nickel plated
Dust cover:	PC, UL94V-2
IDC	Housing: PC+ glass fiber, UL 94V-2 Terminal: phosphor bronze with tin plated
Ground Wire:	18 AWG wire, with green/yellow striped color

ORDERING INFORMATION

Part Code	Description
NPP-C62BLK241	Cat6 STP 24Port Loaded Patch Panel
NPP-C62BLK481	Cat6 STP 48Port Loaded Patch Panel



D-Link (India) Limited
Kalpataru Square, 2nd Floor, Kondivita Lane, Andheri-East, Mumbai-400059
Specifications are subject to change without notice.
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners.
©2010 D-Link Corporation. All rights reserved. Release 01 (May 2010)