

Cat6A UTP Patch Cords

D-Link Cat6A patch cords are high quality four pair twisted stranded cable terminated with RJ45 modular plugs at both the ends. It is TIA/EIA 568C.2 standard. These patch cords are appropriate for high speed data transmission.



SPECIFICATIONS

Conductor:	24 AWG, Multi-cores
Conductor Metal:	Bare Copper
Insulation Material:	HD-PE
Material:	PVC UL94V-0
Color Code:	Cool Grey 5C
Heat Resistance:	75° C minimum (Temperature limited)
Flame Property:	The purpose of the vertical flame test is to screen out flammable wires. It follows the VW-1 (UL) and FT-1 (CSA) standards

MODULAR CONNECTOR/PLUG

RJ-45 8P for transparent color	
Gold Plated:	30U°
Contact Blade:	phosphor bronze
Dielectric withstanding voltage:	500V AC
Insulation Resistance:	35M Ohm (max.)
UL Applications:	250V AC, PC UL94-V-0

Application

10BASE-T, 100BASE-TX Fast Ethernet, 1000BASE-T, 10GBASE-T (IEEE802.3)
100VG-AnyLAN (IEEE802.12)
500MHz Broadband Video
Voice, T1, ISDN
155/622 Mbps ATM
Power over Ethernet (PoE)

ORDERING INFORMATION

CAT6A Patch Cord	
Part Code	Description
NCB-6AUGRYR1-1	Cat6A UTP 24AWG Patch Cord, 1M
NCB-6AUGRYR1-2	Cat6A UTP 24AWG Patch Cord, 2M
NCB-6AUGRYR1-3	Cat6A UTP 24AWG Patch Cord, 3M

D-Link (India) Limited
Kalpataru Square, 2nd Floor, Kondivita Lane, Andheri-East, Mumbai-400059
Specifications are subject to change without notice.
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners.
©2010 D-Link Corporation. All rights reserved. Release 01 (May 2010)